



Features

- Irradiation cross-linked, LSZH insulation
- Heat, Oil, sunlight, & moisture resistant
- Extremely flame retardant
- Rugged, Flexible, Easy to Install
- Easy to strip – has no separator tape
- Circuit Integrity – IEC 60331-830°C x 3hrs with shock
- Flexible Tin-coated conductors for improved terminations and corrosion resistance
- Pigmented insulation with vivid colors
- Better physical and wet electrical properties than halogen free IEC HF cables
- Insulation Resistance Constant, K = 10,000 vs 550 for HF90 per IEC 60092-360
- Limited Smoke, Zero Halogen

Performance Standards

- Listed by UL as Type X110, rated for 110°C
- Listed by Intertek as Type LSX, IEEE 1580 and is rated 90°C
- Passes IEEE 1202 & FT-4 at 70,000 Btu/hr Vertical Tray Flame Tests
- Single conductors pass the UL VW-1 flame test per UL-44/UL-1581
- Passes IEC 60331-830°C x 3 hrs with shock
- Type approved by ABS, DNV GL and Lloyd's Register NA
- Armored & Sheathed cables suitable for Class I, Div. 1 / Zone 1 locations
- Unarmored cables are suitable for Class I, Div. 2 / Zone 2 locations
- IEEE 1580 Tests:
 - Halogen Content – 0% < 0.2%
 - Acid Gas – 0.5% < 2%
 - Smoke Index – 8.85 < 25
 - Toxicity Index – 0.6 < 1.5
- IEC Tests:
 - Passes IEC 60332-1-2 & -2-2 Flame Tests
 - Passes EN 50265-2-1 & -2 Flame Tests
 - Smoke Density, IEC 61034, Light Transmittance = 96%
 - Ph > 4.3, per IEC 60754
 - Conductivity $\leq 10 \mu S \cdot mm^{-1}$, per IEC 60754
 - Halogen Acid, IEC 60754, Pass

Scope

Exane[®] ZH-CI, low smoke zero halogen (LSZH), circuit integrity multi-shielded pairs, Marine Shipboard Cables, bridge the performance gap between the premium Exane-125 Type P cables and the IEC HF cables. These cables are used in safety and emergency shut down systems, UPS systems, communications and PA/GA systems, gas detectors, and fire alarms. The Exane[®] ZH, LSZH insulation is radiation cross-linked and provides outstanding physical properties, resistance to abrasion, cut-through, low and high temperature, sunlight, flame. It is a low-smoke, zero halogen material that is extremely tough and durable and withstands the arduous environmental conditions experienced in offshore LV wind substations, mobile offshore drilling units (MODU), FPSO's & TLP's for oil and gas drilling rigs. It provides the low-smoke, non corrosive characteristics that have been deemed to be critical for the crew quarters in MODU's. Exane[®] ZH is Intertek listed to IEEE 1580 as Type LSX, a low-smoke, zero halogen cable that also meets the IEC HF requirements. It is also listed by Underwriters Laboratories (UL) to UL TC-ER, UL 1309.

Construction

Conductor: AWG – Flexible Tinned Copper, per IEEE 1580. Sq mm – IEC 60228 Class 5 TC. Available on request

Fire Resistant Tape: Mica tape wrapped conductor

Insulation: Irradiation Cross-Linked Exane-ZH, Type LSX (IEEE 1580)

Color Code: As specified by customer. Standard – Black + White + No's

Foil Shields: Aluminum/Polyester foil tape + tinned copper drain wire

Overall Braid Shield: Tinned Copper Braid

Outer Jacket (optional): Black, Irradiation Cross-Linked, LSZH, Type L (IEEE 1580) & Type SHF-2 (IEC)

Temperature Rating: UL – 110°C; IEEE – 90°C
RSCC Wire & Cable – 125°C