



Features

- Wide temperature range -55°C to 110°C*
- Thermoset Insulation and jacket
- Superior mechanical properties
- Flexible construction
- Flame retardant
- Excellent fluid/oil resistance
- Moisture and sunlight resistant
- Employs Exane 1068A insulated conductors
- REACH and RoHS compliant

Performance Standards

- AAR S-501/AAR RP-585
- ICEA S-66-524 (5-95-658)
- Passes the spread of fire and smoke emission in accordance with NFPA 130-2020 article 8.6.7.1.1 FT4/IEEE 1202 with smoke per UL1685
- Meets requirements of 49 CFR Part 238 for flame and smoke requirements
- Meets transit toxicity requirements when tested in accordance with BSS 7239
- Meets transit smoke requirements when tested in accordance with ASTM E662
- Meets APTA PR-E-RP-009-98 2021 publication

Construction

Conductor: Annealed, Tinned copper per ASTM B33, B172, AAR S-501, and AAR RP-585

Insulation: Irradiated Crosslinked polyolefin XLPO Exane®

Circuit Identification: As required

Binder: Polyester tape

Shields: Tin copper braid (optional)

Jacket: Cross-linked polyolefin Exane® Jacket

* RSCC rated 110°C

Scope

Exane® multiconductor transit cables are a rugged, flame retardant construction. They are suitable for installation indoors or outdoors in metal trays, conduit, underground duct, or for direct burial. The cables have excellent flexibility and resist crush, low temperature cracking, moisture and petrochemical fluids. The Exane® thermoset insulation system provides a conductor component with superior cut-through, abrasion resistance and electrical overload characteristics.

Exane[®] Transit Multi-Conductor Cable

Exane: Two conductors shielded (TC braid) with Exane Jacket

Product Code	Number of Conductors	Size AWG	Stranding	Insulated Conductor OD (Inch)	Jacket Thickness (Inch)	Cable OD (Inch)	Weight (lbs. per 1000 ft.)	Technical Drawing
TXE 2/C 18S(Exane)	2	18	19/30	0.109	0.045	0.339	67	TD-002603
TXE 2/C 16S(Exane)	2	16	19/29	0.116	0.045	0.348	74	TD-002604
TXE 2/C 14S (Exane)	2	14	19/27	0.129	0.045	0.374	88	TD-008751
TXE 2/C 12S (Exane)	2	12	19/25	0.147	0.045	0.410	116	TD-003086

Exane: Three conductors shielded (TC braid) with Exane Jacket

Product Code	Number of Conductors	Size AWG	Stranding	Insulated Conductor OD (Inch)	Jacket Thickness (Inch)	Cable OD (Inch)	Weight (lbs. per 1000 ft.)	Technical Drawing
TXE 3/C 18S (Exane)	3	18	19/30	0.109	0.045	0.351	81	TD-002605
TXE 3/C 16S (Exane)	3	16	19/29	0.116	0.045	0.366	92	TD-002606
TXE 3/C 14S (Exane)	3	14	19/27	0.129	0.045	0.400	120	
TXE 3/C 12S (Exane)	3	12	19/25	0.147	0.045	0.438	145	

Exane: Four conductors shielded (TC braid) with Exane Jacket

Product Code	Number of Conductors	Size AWG	Stranding	Insulated Conductor OD (Inch)	Jacket Thickness (Inch)	Cable OD (Inch)	Weight (lbs. per 1000 ft.)	Technical Drawing
TXE 4/C 18S (Exane)	4	18	19/30	0.109	0.045	0.374	92	TD-003085
TXE 4/C 16S (Exane)	4	16	19/29	0.116	0.045	0.402	109	TD-002607
TXE 4/C 14S (Exane)	4	14	19/27	0.129	0.045	0.427	130	TD-008673
TXE 4/C 12S (Exane)	4	12	19/25	0.147	0.045	0.480	187	TD-003801

Exane: Two conductors non shielded with Exane Jacket

Product Code	Number of Conductors	Size AWG	Stranding	Insulated Conductor OD (Inch)	Jacket Thickness (Inch)	Cable OD (Inch)	Weight (lbs. per 1000 ft.)	Technical Drawing
TXE 2/C 18 (Exane)	2	18	19/30	0.109	0.045	0.311	50	TD-006377
TXE 2/C 16 (Exane)	2	16	19/29	0.116	0.045	0.326	55	TD-005309
TXE 2/C 14 (Exane)	2	14	19/27	0.129	0.045	0.351	68	
TXE 2/C 12 (Exane)	2	12	19/25	0.147	0.045	0.395	100	

Exane: Three conductors non shielded with Exane Jacket

Product Code	Number of Conductors	Size AWG	Stranding	Insulated Conductor OD (Inch)	Jacket Thickness (Inch)	Cable OD (Inch)	Weight (lbs. per 1000 ft.)	Technical Drawing
TXE 3/C 18 (Exane)	3	18	19/30	0.109	0.045	0.328	70	TD-006512
TXE 3/C 16 (Exane)	3	16	19/29	0.116	0.045	0.343	73	TD-004426
TXE 3/C 14 (Exane)	3	14	19/27	0.129	0.045	0.371	87	TD-010589
TXE 3/C 12 (Exane)	3	12	19/25	0.147	0.045	0.410	115	

Exane: Four conductors non shielded with Exane Jacket

Product Code	Number of Conductors	Size AWG	Stranding	Insulated Conductor OD (Inch)	Jacket Thickness (Inch)	Cable OD (Inch)	Weight (lbs. per 1000 ft.)	Technical Drawing
TXE 4/C 18 (Exane)	4	18	19/30	0.109	0.045	0.362	74	TD-011689
TXE 4/C 16 (Exane)	4	16	19/29	0.116	0.045	0.375	90	TD-005279
TXE 4/C 14 (Exane)	4	14	19/27	0.129	0.045	0.427	130	
TXE 4/C 12 (Exane)	4	12	19/25	0.147	0.045	0.453	145	



Marmon Electrical
A Berkshire Hathaway Company